

10CTRWH75 – 10 dB Gain WR75 Rectangular Horn Antenna Assembly with Integrated Coax-to-Waveguide Adapter (10–15 GHz)

Attributes

Electrical Specification

Adapter Type	Right Angel
Adapter Grade	Standard
Frequency Band	X-Ku
Waveguide Type	Rectangular
Waveguide Size EI WR	WR75
Min. Frequency (GHz)	10
Max. Frequency (GHz)	15
VSWR Max	1.28
VSWR Min	1
Impedance (Ω)	50
Max. Insertion Loss (dB)	0.27
Min. Insertion Loss (dB)	0.21

Interface

Flange Style	Square
Connector	SMA
Connector Type	Female

Mechanical Specification






Body Material	Al
Finishing	Gray Paint
Operating Temp Low(°c)	-50
Operating Temp High(°c)	80






Overview

The 10CTRWH75 is a WR75 rectangular horn antenna assembly designed for operation over the 10–15 GHz frequency band. The unit integrates a precision-machined rectangular horn with a coax-to-WR75 waveguide adapter, providing a compact and mechanically robust transition from a coaxial interface to free-space radiation. The antenna assembly delivers stable radiation characteristics, nominal gain of 10 dB, and excellent impedance matching with a maximum VSWR of 1.28 across the operating band. The integrated adapter ensures efficient power transfer while minimizing insertion loss and reflection. This design makes the assembly suitable for both measurement environments and high-frequency microwave systems. The antenna supports up to 50 W of continuous input power and 3 kW peak power. It is equipped with an FBP120 (UBR120) flange, Flange No. 120, ensuring secure mechanical mounting and full compatibility with standard WR75 waveguide interfaces. The assembly is manufactured in accordance with CACIRA quality standards to ensure reliable electrical performance and long-term stability.

Results



Drawing



<i>Parameter</i>	<i>Inch (mm)</i>	<i>Parameter</i>	<i>Inch (mm)</i>
<i>A</i>	<i>1.496 (38)</i>	<i>M</i>	<i>0.533 (13.525)</i>
<i>B</i>	<i>0.75 (19.05)</i>	<i>N</i>	<i>0.907 (23.05)</i>
<i>C</i>	<i>0.375 (9.525)</i>		
<i>D</i>	<i>0.118 (3)</i>		
<i>E</i>	<i>1.122 (28.5)</i>		
<i>F</i>	<i>1.040 (26.42)</i>		
<i>H</i>	<i>4.071 (103.413)</i>		
<i>L</i>	<i>1.614 (41)</i>		
<i>R</i>	<i>0.118 (3)</i>		
<i>W</i>	<i>1.319 (33.5)</i>		